

MAIN CONVEYOR

- Belt Length: 39.2 metres
- Belt Width:800mm / 32ins
- Belt Type:800mm EP 400 3 ply belt
- Drum Centres:.....19.1 metres
- Drive drum Diameter:295mm
- Tail drum Diameter:220mm

HYDRAULICS

- Hydraulic Motor..... Danfoss OMT500

CHASSIS

- Tyres.....11.5/80 x 15.3 RIM & TYRE 6 STUD

ALL-ELECTRIC

- 3 phase..... 380 - 415 Volts

ELECTRIC MOTOR

- Type:7.5kw
- Motor rpm:1400 rpm
- Gearbox Torque:1570nm,
- Ratio:7.5kw at 20.23/1 which produces 1022nm
- Output rpm:71

STANDARD MACHINE INCLUDES:

- 30ft Coupling Hose Kit
- Tow Bar and Ground Pivot Stand c/w wheels
- Danfoss Motor
- Hydraulic Angle Adjustment (hydraulic machine only)
- 2.5" Self Lube Triple Seal Bearings
- Varied angle wing rollers

OPTIONS

- Belt: (Chevron / Heavy Duty)
- Anti-Roll Back Flaps
- Power Source: (Diesel Hydraulic / Electric)
- Scraper Upgrade
- Enclosed Skirting
- Feedboot Extension

Standard belt widths available are 800mm / 32ins to 1050mm / 40ins depending on conveyor type.
 All standard conveyors come hydraulically driven and hydraulically raise and lower.